

RELIANCE



HAND OPERATED
CONSTANTLY
HEATED PORTABLE
LAMINATE HEAT SEALER

RELIANCE HAND SEALER

Dedicated to the sealing of coated foils (Barrier films) and coated papers only. Reliance is a precision lightweight reliable manually operated model of constant heat jaw sealer. Manufactured to an industrial specification, designed for continuous use, providing repeatable high-quality seals on the films mentioned above.

The controls are built into the hand set and comprise of an adjustable temperature thermostat and L.E.D. indicators displaying pre-set sealing temperature attained and mains on. Reliance is operated by hand pressure, closing the sealing jaws on the film, transfers heat into the film of the set temperature for the required sealing time. (Refer to the spec sheet of the material for recommended sealing settings).



A degree of care is always necessary with this type of potable sealer as the very hot sealing jaws are exposed.


Reliance provides a broad crimp pattern seal (see inset image). The film contact faces have a Fluoropolymer (P.T.F.E) coating, to aid film packaging release and any plastic residue can be simply wiped away.

RELIANCE is supplied in a power coat finish, other parts of aluminium and engineering plastics. This model being a portable appliance is available in both 230 or 115 volt supply.

NOTE; THIS MACHINE IS **NOT** SUITABLE FOR SINGLE WEBED FILMS (POLYTHENE)

FEATURES

- Both jaws heated.
- Portable.
- · Quick warm up time.
- PTFE Coated Sealing Jaws.
- Lightweight.







TECHNICAL SPECIFICATION

MODEL:	300
Seal Length (mm)	300
Seal Form	Longitudinal Crimp 2.4mm Pitch
Seal Width (mm)	12
Throat Depth (mm)	45
Temperature Range	0-250°C
Power Supply	230 Volts 50 Hz (115 V option)
Warm Up Time	5 Minutes
Power Consumption (Watts)	360
Sealer Dims. Height x Depth x Width (cm)	11 x 35 x 30
Weight Kgs NETT	1.3
Weight Kgs GROSS	3.0

