

## SI Vacuum Med

### Pneumatic vacuum impulse medical sealer validatable according to ISO 11607.2

Pneumatic vacuum impulse sealer, validatable to the ISO 11607.2 and EN 868-5 Directive.

Available in three sealing lengths (550mm, 750mm, 1020 mm).

With support the machine can be put from horizontal to vertical sealing position

Especially designed for pharmaceutical, medical laboratories and chemical industry.

Equipped with Venturi vacuum system.

**Accessories:**

SIS stand adjustable in height, to allows vertical sealing

SIPI working table (only with SIS)

SIPO bag support (only with SIS)

SIRS bag stretcher (only on 1020 version)

**Fully validatable to the ISO 11607.2**

MODEL	SI 520 VACUUM MED	SI 720 VACUUM MED	SI 1020 VACUUM MED
Sealable materials	LDPE/PAPE/ALPE/PAPER MEDICAL LAMINATED, TYVEK <sup>®</sup>		
Sealing	Impulse with Ropex temperature control		
Sealing bars	bi-active (upper bar can be switched off)		
Sealing (mm)	520 x 8	720 x 8	1020 x 8
Construction	Stainless Steel		
Gas flushing	Yes		
Functioning	Pneumatic		
Air pressure	> 6 Bar		
ISO 11607-2 Validation	Yes		
EN 868-5 Conformity	Yes		
DIN 58953-7:2010 Directive	Yes		
Printer	External		
Interfaces	1 RS232 port		
Dimensions (mm) / Weight (kg)	590 x 487 x 241 / 32	790 x 487 x 241 / 34	1110 x 487 x 241 / 37

